

# Graphcal Perforated Vinyl GO1020

Datasheet

## Specifications

## Graphcal Perforated Vinyl GO1020

<b>PVC Type</b>	Calendered monomeric soft PVC film
<b>PVC Thickness</b>	125 microns
<b>PVC Color</b>	White with black reverse side
<b>PVC Shrinkage</b>	Max 0.5mm (48 hours at 70 degrees, Aluminum, MDF)
<b>PVC Opacity</b>	>99%
<b>PVC Hole Diameter</b>	1.6mm
<b>PVC Distance Between Holes</b>	2.4mm
<b>PVC Hole Coverage</b>	40%
<b>Adhesive Type</b>	Clear Acrylic Solvent, removable pressure sensitive glue
<b>Adhesive Weight</b>	20 ± 2 g/m <sup>2</sup>
<b>Initial Adhesion (20mins)</b>	4±2N/inch FTM1
<b>180 degree Peel (24hr)</b>	6±2N/inch FTM1
<b>Removable Durability</b>	6 months
<b>Liner Type</b>	Double layer composite paper
<b>Liner Color</b>	White
<b>Liner Weight</b>	155g ±5g
<b>Liner Release Force</b>	40g
<b>Packaging</b>	Carton box
<b>Storage Time</b>	12 months under ordinary conditions at temperature of 22°C (72°F) and relative humidity of 50-55%
<b>Sizes</b>	54" x 100' (1.37m x 30.4m)
<b>Applications</b>	One way vision media is utilized in digital UV, solvent, eco-solvent and Silk Screen printing for signage displays, vehicle and subway graphics, window and glass wall decoration.

All the above information is true based on laboratory analysis. Nonetheless, the manufacturer is not liable to any claims or compensation due to this data.