

OneSign Floor Graphics Film

Datasheet

Specifications

OneSign Floor Graphics Film

Media:	Anti-slip PVC
Production description:	Floor Graphics Film is an 180 micron anti-slip matte PVC film with acrylic pressure sensitive adhesive. Applied on laminating floor image against slip and damage while stepping on it.
Features:	Floor Graphics is a thick PVC film with chemical processing to make the surface rough and slip-resistant. Excellent Adhesion on graphic media. The film renders good protection against moisture and is washed with water easily.
Vinyl specification:	Composition: monomeric calendered PVC Thickness of vinyl: 180 microns Weight: 265gsm Surface: matte slip-resistant
Release liner	100gsm Release strength: 15g/inch
Solvent acrylic adhesive:	Pressure sensitive Glue thickness : 25 mic. Adhesive: permanent
Standard size:	50"(1.27m) x 164' (50m)
Shelf life:	24 months
Packaging:	1 roll per box, 3" (76mm) core.
Shrinkage:	Shrinks by 1% without printed ink outdoors for one year.
Storage condition:	Keep all finished rolls in horizontal position, avoid direct sunlight. Recommended storage between temperature 15° - 25°C (59° - 77°F) 35-65% relative humidity.

All the above information is true based on laboratory analysis. Nonetheless, the manufacturer is not liable to any claims or compensation due to this data.