

OneSign Vinyl Film UPX7000

Datasheet

Specifications

OneSign Vinyl UPX7000

PVC Type:	Calendered polymeric soft PVC film
PVC Thickness:	60 microns
PVC Color:	Ceramic white
PVC Shrinkage:	$\leq 0.6\%$
PVC Surface Tension:	$\geq 30\text{dn/cm}$
PVC Opacity:	$>80\%$
Adhesive Type:	Grey solvent based removable pressure sensitive glue
Adhesive Weight:	25 g/m ²
Adhesion Temperature:	from 15°C ~ 40°C (59°F ~ 104°F)
Adhesive Peeling Force:	$\geq 7\text{N}/25\text{mm}$ 20min
Adhesive Holding Power:	$\geq 3000\text{min}$
Liner Type:	Bubble-free embossed Kraft paper
Liner Color:	White
Liner Weight:	145 g
Liner Release Force:	0.1~0.6N/4cm
Durability:	1 year
Packaging:	Carton box
Storage time:	12 months under ordinary conditions at temperature of 22°C (72°F) and relative humidity of 50-55%
Size:	54" x 164' (1.37m x 50m)
Applications:	Outdoor digital and silk screen printing media for signage display, vehicle graphics, airport and subway graphics applications.

All the above information is true based on laboratory analysis. Nonetheless, the manufacturer is not liable to any claims or compensation due to this data.