

Graphcal Vinyl Film G3000

Datasheet

Specifications

Graphcal Vinyl Film G3000

PVC Type:	Calendered monomeric soft PVC film
PVC Thickness:	80 microns
PVC Color:	White
PVC Shrinkage:	≅ 0.8%
PVC Surface Tension:	≅ 30dn/cm
PVC Opacity:	>80%
Adhesive Type:	Gray solvent based removable pressure sensitive glue
Adhesive Weight:	16 g/m ²
Adhesion Temperature:	From 15°C ~ 40°C (59°F ~ 104°F)
Adhesive Peeling Force:	≅ 6.5N/25mm 20min
Adhesive Holding Power:	≅ 800min
Liner Type:	Kraft paper
Liner Color:	White
Liner Weight:	140 g
Liner Release Force:	0.1~0.6N/4cm
Durability:	1 year
Packaging:	Carton box
Storage time:	12 months under ordinary conditions at temperature of 22°C (72°F) and relative humidity of 50-55%
Size:	54" x 164' (1.37m x 50m)
Applications:	Outdoor digital and silk screen printing media for signage display, vehicle graphics, airport and subway graphics applications.

All the above information is true based on laboratory analysis. Nonetheless, the manufacturer is not liable to any claims or compensation due to this data.