

# OneSign Twill Floor Graphics Film

Datasheet

## Specifications

## OneSign Twill Floor Graphics Film

<b>Composition:</b>	Monomeric calendered vinyl, PEK release paper
<b>Film thickness:</b>	200 micron
<b>Weight of release paper:</b>	100+/-10g/sqm
<b>Sizes:</b>	1.27m (50") x 50m (164')
<b>Length tolerance:</b>	+/-200mm
<b>Width tolerance:</b>	+/- 5mm
<b>Temperature range:</b>	from -40°C ~ +80°C (-40°F ~ +176°F)
<b>Packing:</b>	Carton box
<b>Storage time:</b>	1 year
<b>Durability:</b>	6 months*
<b>Applications:</b>	Provides scuff-resistant and non-slip protection for floor graphics. Ideal for supermarkets, car dealers, airports, subways, fast food restaurants and general retail advertising. It creates a durable surface that can be washed and waxed.
<b>Caution:</b>	Any floor surface that is wet due to rain, snow or other contaminants may become slippery with or without floor graphics film.

\*The performance statement are based upon foot traffic experience in the field. Graphics may be damaged by pallets or heavy equipments such as forklifts.

Performance depends upon preparation of the floor before application, exposure conditions and maintenance of the graphics

All the above information is true based on laboratory analysis. Nonetheless, the manufacturer is not liable to any claims or compensation due to this data.



Datasheet - 2015/08, Rev. 1