

Graphcal Vinyl Film MX2100

Datasheet

Specification

Graphcal Vinyl Film MX2100

PVC Type:	Calendered monomeric soft PVC film
PVC Thickness:	100±10 microns
Surface	Matte
PVC Color:	White
PVC Shrinkage:	≤0.8%
PVC Surface Tension:	≥30dn/cm
PVC Opacity:	>95%
Adhesive Type:	Permanent gray pressure sensitive glue not removable
Adhesive Weight:	35±5 g/m2
Adhesion Temperature:	From 15°C ~ 40°C (59°F ~ 104°F)
Adhesive Peeling Force:	≥10N/25mm
Adhesive Holding Power:	≥1440min
Adhesion-Ball Tack	≥5N/25mm*25mm
Liner Type:	Bubble free kraft embossed paper
Liner Color:	White
Liner Weight:	140g±10g/m²
Liner Release Force:	0.05~0.2N/25mm
Durability:	3 years
Packaging:	Cardboard box
Storage time:	12 months under ordinary condition at temperature of 22°C and relative humidity of 50-55%
Size:	54" x 150' (1.37m x 45.70m)
Applications:	Outdoor digital and silk screen printing media for signage display, vehicle graphics, airport and subway graphics application.

All the above information is true based on laboratory analysis, Nonetheless, the manufacturer is not liable to claims or compensation due to this data.