

10 Oz Laminated Frontlit Banner Matte White / White Data Sheet



Our banners are matte and glossy white, and all of them are smooth PVC banners. Their calendered vinyl provides superior print resolution and image quality. It is optimized to work with pressure-sensitive lms, screen printing and inkjet applications. Contains excellent strength properties that makes it suitable for nearly all types of exterior applications.

PROPERTIES	DATA	UNIT	TEST METHOD
Base Fabric	Denier (High tenacity yarn) 100%PES	200DX300D	DIN EN ISO2060
Construction	knitting /inch	18 x 12	DIN60001
Weight of fabric	G/m2	42±5	DIN53352 Bs3424 Method5B
Weight of PVC	G/m2	298±5	DIN53352 Bs3424 Method5B
Total weight	Oz/y2 (G/m2)	10 oz (340 g)	DIN53352 Bs3424 Method5A
Thickness	mm	0.26±0.02	DIN EN ISO 2286-3
Breaking Strength	N/5cm	Warp 490 Weft300	DIN53354 Bs3424 Method6A
Tearing Strength	N	Warp 45 Weft35	DIN53356 Bs3424 Method7A
Adhesion	N/5CM	60	DIN53357 Bs3425 Method9B
Width	126" x 150' (3.20m x 45.70m)		
Temperature Range	-20° C ~ 70° C / -68° F ~ 158° F		
Shelf life	2 years from factory shipment		

Avoid excessive moisture, temperatures and direct sunlight

AREAS OF USE

- Billboards
- Displays (outdoors and indoors)
- Banner
- Building murals and store displays



Data sheet - 07/2018

The information contained herein is subject to change without notice