

Matte White Smooth Wall Covering

Datasheet

Specifications

GS1020M Matte White Smooth Wall Covering

PVC Thickness:	0.405±0.025 mm
Inside Diameter of Rolls:	75 mm
Basic Weight:	360±30 g/m2
Thickness Base:	0.120±0.010 mm
Thickness Emboss:	0.250±0.030 mm
Glue Clear Thickness:	Acrylic 0.040±0.005
Liner Thickness:	80gsm-Double Side PE 0.145±0.015 mm
Ball Tack:	7↑
Storage Condition:	from 5°C ~ 40°C (-104°F ~ +212°F)
180° Peel Adhesion:	g/25mm-20min 1000↑ / g/25mm-24hr 1300↑
90° Release Force:	g/50mm 50±30
Holding Power:	0.5↓ mm
Tensile Strength:	g/10mm 2000↑
Elongation:	150↑ %
Shrinking:	% (80°Cx48hrs) 1↓
Opacity:	75↑
Glossy:	Degree/60°Angle 5±3
Heat Resistance:	80 °C (176°F)
Cold Resistance:	-30 °C (-22°F)
Size:	48" x 150' (1.22m x 45.7m)
Durability:	1 Year
Applications:	Short-term solvent, eco-solvent and silkscreen printing for outdoor signage, decoration and advertising

All the above information is true based on laboratory analysis. Nonetheless, the manufacturer is not liable to any claims or compensation due to this data.