

# **PERFORMANCE GUIDE**

## **Represents Typical Values Only**

www.mactac.com

Revision: 04/2021 BJC

### ULTRA SLAPSHOT REMOVABLE ACRYLIC PRODUCT CODE: 3-9292

#### PRODUCT DESCRIPTION

6-mil Matte white vinyl with removable solvent adhesive that is printable with solvent, eco-sol, latex and UV ink jet. Excellent for use in point-of-purchase, trade show displays and window graphics.

#### **APPLICATIONS**

- Window Graphics
- Point of Purchase

#### FEATURES AND BENEFITS

- 6.0-mil matte white semi-rigid vinyl, removable adhesive, 90# poly-coated layflat liner.
- Compatible with a variety of printing methods including solvent, eco-solvent, latex and UV ink jet.
- Mactac recommends leaving a 1/4 of an inch border around your graphic when printing.
- Mactac recommends at least 24 hours of cure time before cutting.
- 1-year clean removability under normal conditions.

#### TECHNICAL DATA

Face Material 6.0-mil semi-rigid vinyl

Color and Finish Matte White Adhesive 50, Removable

Liner 90# poly-coated bleached layflat

#### TYPICAL CHARACTERISTICS

15 min. Average Adhesion Values 24 hr. (PSTC-1, 180° peel @ 12"/min., 73°F, on Stainless Steel) 24 oz. 35 oz. 50°F

Minimum Application Temperature

Service Temperature Range -40°F to +180°F

Shelf Life (@ 73°F, 50% RH) 1 year Outdoor Durability 5 years

#### CHEMICAL RESISTANCE

Distilled Water (24 hr)	No Effect
Detergent (24 hr)	No Effect
10% HCl (10 min)	No Effect
10% Ammonium Hydroxide (10 min)	No Effect
Anti-Freeze (24 hr)	No Effect
SAE 20 Motor Oil (24 hr)	No Effect
Gasoline (1 hr)	No Effect

IMPORTANT NOTICE: The information given, and the recommendations made herein are based on our research and are believed to be accurate, but no guarantee of their accuracy or completeness is made. In every case, user shall determine before using any product in full scale production, or in any way, whether such product is suitable for user's intended use for their particular purpose under their own operating conditions. User assumes all risk and liability whatsoever in connection with their use of any product. The products discussed herein are sold without any warranty as to merchantability or fitness for a particular purpose, or any other warranty, express or implied. No representative of ours has any authority to waive or change the foregoing provisions, and no statement or recommendation not contained herein shall have any force of effect unless in an agreement signed by the officers of seller and manufacturer. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement, or recommendation to practice any invention covered by any patent without authority from the owner of the patent. The following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace or credit such quantity of the product proved to be defective at its discretion.

<sup>™</sup> Trademark of Morgan Adhesives Company. ® Registered Trademark of Morgan Adhesives Company.

