

SID XPRESS

Datasheet



Parameters

SID XPRESS 320-8H

Printhead	SEIKO • 510 nozzles • 50 picoliters										
Number of printheads	8 printheads										
Resolution	Up to 720 dpi										
Ink <ul style="list-style-type: none"> ● Type ● Colors ● Capacity 	Solvent or Eco Solvent										
	CMYK										
	Main tanks: 1 or 5 liters per color + flush										
Media <ul style="list-style-type: none"> ● Max. printing width ● Feeding System ● Types 	126" (3,200 mm)										
	Roll or sheet (max. media weight: 264 lbs - 120 kg)										
	Vinyl, perforated vinyl, polyester, banner or canvas										
Print Speed up to	<table border="0"> <tr> <td>Draft</td> <td>2,818 sq.ft./h (262 m²/h) • 1 pass</td> </tr> <tr> <td>Standard 1</td> <td>1,689 sq.ft./h (157 m²/h) • 2 pass</td> </tr> <tr> <td>Standard 2</td> <td>1173 sq.ft./h (109 m²/h) • 3 pass</td> </tr> <tr> <td>Quality 1</td> <td>914 sq.ft./h (85 m²/h) • 4 pass</td> </tr> <tr> <td>Quality 2</td> <td>753 sq.ft./h (70 m²/h) • 4 pass</td> </tr> </table>	Draft	2,818 sq.ft./h (262 m ² /h) • 1 pass	Standard 1	1,689 sq.ft./h (157 m ² /h) • 2 pass	Standard 2	1173 sq.ft./h (109 m ² /h) • 3 pass	Quality 1	914 sq.ft./h (85 m ² /h) • 4 pass	Quality 2	753 sq.ft./h (70 m ² /h) • 4 pass
Draft	2,818 sq.ft./h (262 m ² /h) • 1 pass										
Standard 1	1,689 sq.ft./h (157 m ² /h) • 2 pass										
Standard 2	1173 sq.ft./h (109 m ² /h) • 3 pass										
Quality 1	914 sq.ft./h (85 m ² /h) • 4 pass										
Quality 2	753 sq.ft./h (70 m ² /h) • 4 pass										
Cleaning System	Automatic Individual Positive Pressure System										
Heating and Cooling System	Preheater, platform heater, front heater, two front infrared heaters and a powerful fan system										
Interface	USB 2.0										
Noise Level	Printing: < 70 dB • Standby: < 40 dB										
RIP Software	Photo PRINT 10										
Voltage	AC 220 V, 50 Hz / 60 Hz										
Power Consumption	7,560 W • 35 A										
Operational Temperature	Temperature 68 - 82°F (20 - 28°C) Humidity 40% - 60%, non-condensing										
Equipment dimensions (Length x Width x Height)	200" x 41" x 66" (5,080 x 1,040 x 1,670 mm)										
Package dimensions (Length x Width x Height)	207" x 48" x 77" (5,250 x 1,210 x 1,950 mm)										
Equipment weight	Net Weight 2,013 lbs (913 kg) Gross Weight 2,866 lbs (1300 kg)										