

Vista 180T


Datasheet



Parameters

Vista 180T


Printhead	EPSON • 3.5 • 7 • 14 picoliters			
Number of Printheads	2			
Resolution	Up to 1440 dpi			
Ink	Type	Water based		
	Colors	4 Colors (CMYK)		
	Capacity	1 liters per color		
Media	Max. printing width	71" (1,800 mm)		
	Max. media width	71" (1,800 mm)		
	Auto Media Feeding System	Max. Media Roll Weight 110 lbs (50 kg)		
	Types	48 ~ 120g Heat Transfer Paper		
Print Speed	Draft	2 passes	High Speed Mode 2 dots	High Quality Mode 3 dots
		3 passes	882 sq.ft./h (82 m ² /h)	676 sq.ft./h (63 m ² /h)
	Standard	3 passes	699 sq.ft./h (65 m ² /h)	505 sq.ft./h (47 m ² /h)
		Quality	4 passes	538 sq.ft./h (50 m ² /h)
Pre Heating and Drying System	Infrared and Cooling Fans			
Cleaning system	Auto Ink Supply System			
Maximum Carriage Height	Up to 0.23" (1.5 to 10 mm from Media)			
Interface	USB 3.0			
Software de Ripeo	PhotoPrint OEM or MainTop RIP. FlexiPrint 19 Optional			
Voltaje	AC 220 V, 50 Hz / 60 Hz			
Power consumption	Heater 7,900W (35.7A) Printer 510W (2.7A)			
Operating temperature	Temperature 20°C - 28°C (68°F - 82°F) Humidity 40% - 60% - no-condensing			
Equipment dimensions (length x width x height)	116" x 48" x 34" (2,960 x 1,228 x 858 mm)			
Package dimensions (length x width x height)	125" x 43" x 33" (3,190 x 1,100 x 845 mm)			
Equipment weight	553 lbs (251 kg)			
Package weight	944 lbs (428 kg)			



Special platform designed for transfer paper




Media sensor



New designs capping station



User friendly control panel



Linear guide rail