

Apollo UV 2513-G6

Datasheet






Parameters

Apollo UV 2513-G6

Printhead	RICOH Gen6 Printhead • Variable Dot 5 • 10 • 15 picoliters	
Number of printheads	2 / 6 Pieces	
Resolution	up to 1200 dpi	
Ink	Types	UV
	Colors	4 colors(CMYK) / White and Varnish is optional)
	Capacity	1 liters
Media	Max. printing width / Max. media width	98" x 51" (2,500mm x 1,300mm) / 98" x 51" (2,500mm x 1,300mm)
	Feeding System	Vacuum Table
	Media Types	PS Board, KT Board, PVC Foam Board, Acrylic, Aluminum, Glass, etc.

Printhead Configuration



Print speed	Draft	4 passes	538 sq.ft./h (50 m ² /h)	1,054 sq.ft./h (98 m ² /h)	1,593 sq.ft./h (148 m ² /h)
	Standard	6 passes	355 sq.ft./h (33 m ² /h)	699 sq.ft./h (65 m ² /h)	1,022 sq.ft./h (95 m ² /h)
	Quality	8 passes	236 sq.ft./h (22 m ² /h)	484 sq.ft./h (45 m ² /h)	699 sq.ft./h (65 m ² /h)

Cleaning System	Negative pressure system and individual color purge controls
Maximum Carriage Height	3.93" (100mm)
Interface	High Speed Ethernet
RIP Software	Flexi Print 21
Voltage / Power Consumption	AC 220 V, 50 Hz / 60 Hz / Total Power 5,500W (35A)
Operating Temperature	Temperature 20°C - 28°C (68°F - 82°F) Humidity 40% - 60% - no-condensing
Equipment dimensions / Package dimensions (L x W x H)	178" x 85" x 58" (4,510 x 2,170 x 1,480 mm) / 186" x 90" x 65" (4,720 x 2,280 x 1,660 mm)
Equipment weight / Package weight	2,094 lbs (950 kg) / 2,811 lbs (1275 kg)

